 ARAUCO. Aserraderos Arauco S.A	SAFETY DATA SHEET	Reference	:	
		Date	:	04.08.2005
Quality Control Department	WHITE WATER-BASED PAINT	Section	:	REMA.
		Page	:	01 of 02
		Versio	:	V 1.0

SECTION I: PRODUCT AND COMPANY INFORMATION

Product Name : White water-based paint
Chemical Class : Paint
Synonym : Paste
Application : Moulding Primer
Supplier : ASERRADEROS ARAUCO S.A.
Address : Los Canelos 71, San Pedro de la Paz, Concepción
CHILE – SOUTH AMERICA
Phone Number : (56) 2 – 6 77 72 00
Fax : (56) 2 – 6 98 59 67
Emergency Phone Number : (56) 41 – 92 26 00

SECTION II: PAINT COMPOSITION AND INGREDIENTS

Polyvinyl Acetate (PVA) : 15% to 20%
Calcium Carbonate : 65% to 70%
Water : 5% to 15%
Titanium Dioxide (TiO₂) : 1% to 5%
Dispersing agent for pigments : 0.3% to 0.4 %
Glycerin : 0.4 % to 0.6%
Surfactant : 0.2% to 0.3%

SECTION III: PHYSICAL AND CHEMICAL INFORMATION OF PAINT


Color : White
Aspect : Viscous liquid
Solid percentage : 70% a 75%
Viscosity (6,30,30) : 26000 cps
Ph : 8 to 9
Density (100 ml/20° C) : 1.707 gr/cc

SECTION IV: EXPLOSIVE AND FIRE HAZARD INFORMATION

This is a non-flammable product. Its combustion generates carbon oxides. It is recommended this product is kept in a ventilated environment and away from sources of heat.

SECTION V: HEALTH HAZARD INFORMATION

Inhalation : There are no known hazards associated with the inhalation of this product.
Ingestion : Its ingestion may cause vomiting, abdominal pains and/or diarrhea
Skin Contact : May cause skin irritation
Eye Contact : May cause eye irritation

 ARAUCO. Aserraderos Arauco S.A	SAFETY DATA SHEET	Reference : Date : 04.08.2005 Section : REMA.
Quality Control Department		WHITE WATER-BASED PAINT

SECTION VI : FIRST AID PROCEDURE

Inhalation : In case of inhalation no special precautions are necessary.
Ingestion : Remove product from stomach through vomiting and contact a physician
Skin Contact : Wash affected area with abundant water for at least 10 minutes. If discomfort appears contact a physician.
Eye Contact : Wash eyes with abundant water for at least 20 minutes. Make sure to keep eyelids open to perform a correct cleansing.

SECTION VII: STORAGE AND HANDLING

Handling : Although it is a very low-hazard product, it is recommended that it is manipulated with protective gloves and goggles. Avoid prolonged contact with skin
Keep container well closed.
Storage : Store in ventilated places.

DISCLAIMER

The information contained in this document is precise and comes from qualified sources. It shouldn't be interpreted as a guarantee of representation for which Aserraderos Arauco S.A. assumes any legal responsibility. This information is only offered for the user's knowledge. The user must determine that any use of this information is in accordance to federal, state and local laws and regulations.